

MUTHAYAMMAL ENGINEERING COLLEGE

(An Autonomous Institution)

(Approved by AICTE, New Delhi, Accredited by NAAC & Affiliated to Anna University) Rasipuram - 637 408, Namakkal Dist., Tamil Nadu.



## MUST KNOW CONCEPTS

:

Viva Voce

2020-21

MECH

Course Code & Course Name :

Year/Sem/Sec

Г

Applied hydraulics and Pneumatics II / IV / A

	UNIT – I FLUID POWER SYSTEMS AND FUNDAMENTALS				
S.No	Term	Notation Symbol)	Concept/Definition/Meaning/Units / Equation/Expression	Units	
1	Fluidpower		Fluid power technology is a means to convert, transmit, control and apply fluid energy to perform useful work		
2	Hydraulics		Hydraulics is used for the generation, control, and transmission of power by the use of pressurized liquids		
3	Pneumatic		The compressed air or pressurized gas is usually filtered and dried to protect the cylinders, actuators, tools and bladders performing the work.		
4	Applications of fluid power		Agriculture, Aviation, Fabrication industry, Machine tools, Oil industry and Pharmaceuticals.		
5	Primary functions of hydraulic fluid		<ul><li>(i) Transfer fluid power</li><li>efficiently.</li><li>(ii) Lubricate the moving parts.</li></ul>		
6	Properties of a hydraulic fluid		Viscosity, Viscosity Index ,Oxidation stability, Demulsibility, Flash point and fire point		
7	Problems of high viscous oil.		<ol> <li>The viscous oil may not be able to pass through the pipes</li> <li>The consumption of power will increase.</li> </ol>		
8	Problems of low viscous oil.		<ol> <li>The internal and external leakage will increase.</li> <li>It cannot lubricate properly and will lead to rapid wear of the moving parts.</li> </ol>		

9	Viscosity Index		The rate of change of viscosity with temperature is indicated on an arbitrary scale called Viscosity Index	
10	Demulsibility		The ability of a hydraulic fluid to separate rapidly from moisture and successfully resist emulsification is known as demulsibility.	
11	Neutralization number of hydraulic fluid		The neutralization number is a measure of acidity or alkalinity of a hydraulic fluid.	
12	Examples of Fire resistant fluids		(i)Water glycols (ii) Water oil emulsions (iii) Phosphate esters	
13	Types of Fluid logic system		AND/NAND, OR/NOR, and FLIPFLOP, logic capability.	
14	What does the circular symbol denotes in hydraulic and pneumatic circuits?		Pump, Motor	
15	What does the square symbol denotes in both hydraulic and pneumatic circuits?		One square - pressure control function. Two or three adjacent squares - directional control.	
16	What does the diamond symbol denotes in both hydraulic and pneumatic circuits ?		Diamond - Fluid conditioner (filter, separator, lubricator, heat exchanger)	
17	What does Triangle Symbols in both hydraulic and pneumatic devices denotes?		Solid - Direction of Hydraulic Fluid Flow Open - Direction of Pneumatic flow	
18	Draw the Symbols of rotary actuator used in both hydraulic and pneumatic circuits	(hydraulic) (hydraulic) ( pneumatic)	-	
19	Symbol used for Single acting cylinder			
20	Symbol used for Double acting cylinders			
21	Symbol used for Directional control valve (2 ports / 2 positions) is			
22	Symbol used for Directional control valve (3 ports / 2			

	positions)			
23	Symbol used for Directional control valve (4 ports / 2 positions)			
24	Symbol used for Directional control valve (4 ports / 3 positions)			
25	Symbol used for Shuttle valve			
	UNIT I	II HYDRAULIC SY	STEM & COMPONENTS	
26	Basic components of hydraulic system		(i)Pump (ii) Hydraulic Valves (iii)Hydraulic actuators	
27	Positive displacement pump		Positive displacement pump, the outlet flow is independent of system pressure	
28	Function of pump in a hydraulic system		A pump converts mechanical energy into hydraulic energy. Mechanical energy is given to the pump via a prime mover such as an electric motor.	
29	Types of positive displacement pumps		Gear pumps, Vane pumps, Piston pumps	
30	Types of gear pumps		External gear pump , Internal gear pump ,Lobe pump, Screw pump	
31	Types of vanepump		Unbalanced vane pump, Balanced vane pump.	
32	Balanced vane pump		Balanced vane pump, there are two inlet and outlet ports which are diametrically opposite to each other. Because the pressure ports are opposite to each other, a complete hydraulic balance is achieved.	
33	Two types of piston pumps		Axial piston pump, Radial piston pump.	
34	Volumetric efficiency of pump	QA/QT	Actual flow rate produced by the pump/ Theoretical flow rate the pump should produce.	
35	Overall efficiency of pump		Volumetric efficiency x Mechanical efficiency.	
36	Hydraulic actuator		The actuator is a hydraulic element which converts the pressure energy of the fluid into mechanical energy.	

	1	1 TT 1 1 4	
37	Types of hydraulic actuators	<ul><li>1.Hydraulic motorcontinuous rotary motion</li><li>2.Semi-rotary actuator-limited angle movement</li></ul>	
		3. Hydraulic cylinder-linear motion.	
38	Types of hydraulic motors	<ol> <li>Gear type hydraulic motors</li> <li>Vane type hydraulic motors</li> <li>Piston type hydraulic motors</li> </ol>	
39	External gear motors uses.	External gear motors are used when relatively high speed and low torque is needed	
40	Single acting cylinder uses	The single acting cylinder is retracted using gravity or by the inclusion of a compression spring at the rod end of single acting cylinder	
41	Mechanical efficiency of a pump	Theoretical power required to operate the pump / Actual power delivered to the pump	
42	Overall efficiency of apump	Power output by the pump/ Actual power input to the pump	
43	Volumetric efficiency of a hydraulicmotor	Theoretical flow rate required to drive the motor/ Actual flow rate into the motor	
44	Mechanical efficiency of a hydraulic motor	Actual power given by the motor/ Theoretical power delivered by the motor	
45	Cylinder	A cylinder is one of the most basic curved geometric shapes, with the surface formed by the points at a fixed distance from a given line segment, known as the axis of the cylinder	
46	Tandem Cylinder	The same amount of fluid and force is used to move the piston a certain distance in either direction. Tandem Cylinders. A tandem actuating cylinder consists of two or more cylinders arranged one behind the other but designed as a single unit.	
47	Telescoping cylinder	A telescoping cylinder is a cylinder employing several pistons which telescope into each other. This cylinder is used where a relatively long working stroke is needed for a short cylinder length.	
48	Pressure-reducing valve	The operation of a pressure-reducing valve that uses a spring-loaded spool to control the downstream pressure.	

	1		
49	Counter balance valve	The purpose of a counterbalance valve is to maintain control of a vertical cylinder to prevent it from descending due to gravity. The primary port of this valve is connected to the bottom of the cylinder, and the secondary port is connected to a directional control valve. (DCV) Flow control valves are used to	
50	Flow Control Valves	regulate the speed of hydraulic cylinders and motors controlling the flow rate to these actuators	
	UNI	Γ III: DESIGN OF HYDRAULIC CIRCUITS	
51	Function of relief valve in a hydraulic system	The function of a relief valve is to limit the system pressure to a specified maximum value by diverting the pump flow back to the tankThe unloading valve is useful to	
52	Function of an unloading valve	control the amount of flow at any given time in systems having more than one fixeddelivery pump.	
53	Function of a sequencevalve	Sequence valves are used to perform number of operations one after the other after the set pressure is reached.	
54	Pressure reducing valve uses	Pressure reducing valve is used to maintain reduced pressure in specified locations of hydraulic system.	
55	Application of a counterbalance valve	The counterbalance valve is used to maintain back pressure on a vertical cylinder to prevent it from falling due to gravity.	
56	Check valve	The check valve is a one way valve, which allows flow in one direction, on the other direction the flow is not permitted	
57	3 - Way valves	The purpose of a 3-way control valve is to shut off water flow in one pipe while opening water flow in another pipe, to mix water from two different pipes into one pipe.	
58	Actuation valve	A valve actuator is a mechanical device that uses a power source to operate a valve. This power source can be electric, pneumatic (compressed air), or hydraulic (the flow of oil)	
59	Solenoid valve	A solenoid valve is an electromechanically operated valve.	

		Solenoid valves differ in the characteristics of the electric current they use, the strength of the magnetic field they generate, the mechanism they use to regulate the fluid	
60	What is the purpose of 3 position-4 way closed center solenoid operated direction control valve.	A 3-position, 4-way valve stops an actuator or allows it to float. A 3-position, 4-way valve is more common in hydraulic circuits.	
61	3 - ways of applying flow controlvalves	Meter-in, Meter-out, Bleed-off.	
62	Intensifier	An intensifier is a device which converts low pressure fluid power into high pressure fluid power	
63	Accumulator	An accumulator is a device that stores potential energy of an incompressible fluid held under pressure by an external source against some dynamic force.	
64	Types of accumulators	Weight loaded type, Spring loaded	
65	Hydrostatic drive	type , Gas loaded type.A hydrostatic drive consists of a positive displacement pump, driving a positive displacement hydraulic motor	
66	Applications of Filter	1.Filter Circuits are used to eliminate background Noise 2.They are used in Radio tuning to a specific frequency 3.Used in Pre-amplification, Equalization, Tone Control in Audio Systems.	
67	Sequencing circuits	Sequencing circuits automatically move actuators in a predetermined sequence. Electrical control - Limit switches moment actuated by the cylinders control the solenoid valves	
68	Difference between hydraulic tubing and hoses	Tubes are constructed of cold drawn steel and they are used where high pressures are encountered. Hose is made up of rubber or thermoplastic tube reinforced with steel wire or textile braiding.	
69	List the parameters affecting the selection of a pump	Maximum operating pressure, maximum delivery, pump drive speed, type of fluid, fluid contamination, pump pulsation, pump noise, size and weight of pump, efficiency and cost	
70	Function of a fluid Reservoir	1.To provide a chamber in which any change in volume of the fluid in the	

	1	
		hydraulic circuit can be
		accommodated.
		2. To provide a radiating surface for allowing the fluid to cool
		allowing the fluid to cool
<u> </u>		A synchronous circuit is a digital
		circuit in which the changes in the
		state of memory elements are
71	Synchronous circuit	synchronized by a clock signal. In a
		sequential digital logic circuit, data is
		stored in memory devices called flip-
		flops or latches.
		Quick exhaust valves are valves that are designed to allow direct exhaust or
		are designed to allow direct exhaust or expulsion of compressed air, the
72	Quick exhaust valves	displacement speed of the cylinder rod
12		increases which reduces the cycle
		time.
		Air control valves are fundamental
		components of any pneumatic system.
72	Air control values	Selecting the right air control valves
73	Air control valves	to regulate system pressure, direction
		of flow, and rate of flow is crucial
		when designing fluid power circuit.
		A pneumatic lubricator injects an
		aerosolized stream of oil into an air
74	Lubricator Unit	line to provide lubrication,
		A lubricator should always be the last
		element in an FRL (Filter-Regulator-
	<u> </u>	Lubricator) unit.A device for controlling the rate of
		working of machinery or for
75	Regulator	controlling fluid flow, in particular a
15		handle controlling the supply of steam
		to the cylinders of a steam engine.
	UNIT IV. PNFIIM	ATIC SYSTEMS AND COMPONENTS
		Strainer is a device for the removal of
		solids from a fluid wherein the
76	Strainer	resistance of motion of such solids is
I		in a straightline
		Filter that removes particles and
		impurities from the air ,to improve the
77	Filter	quality of circulating air by filtering
77	Filter	out impurities Once the air is returned
		to the furnace fan, it is pulled through
		air filters to remove dust and dirt
		Woven wire cloth, Paper filter,
78	Filter media	Woven cloth media, Sintered metal
	ļ	powders, Ceramic and plastic media
-		Piston type motors -Axial, Radial
79	Types of air motors	Vane type motors-Non-reversible,
		Reversible and Turbinemotors

80	Running torque		Torque generated when the motor is rotating at a particular speed	
81	Starting torque		The maximum torque the motor can produce when starting under load	
82	Stall torque		The torque required to stop the motor at a particular supply pressure	
83	Purpose of a two- pressure valve		The two-pressure valve delivers an output when both input signals are present.	
84	Purpose of a shuttle valve		The shuttle valve delivers an output when one input is present or when both are present	
85	Graphic symbol of Four-way, two position DCV		-	
86	Graphic symbol of Five-way, two positionDCV		-	
87	Need for mufflers		The muffler is used to reduce the energy of exhausted air, thereby reducing the noise	
88	F-R-L unit	-[].	F-R-L unit is a combined unit of Filter-Regulator-Lubricator	
89	Purpose of a pressure regulator		The purpose of the pressure regulator is to regulate the incoming pressure to the desired pressure	
90	Multistage compressor		A compressor that draws in air and compress it to its final pressure in two or more stages is called multistage compressor	
91	Filtering methods used in hydraulic system		Surface type, Depth type, Edge type	
92	Suction cups		Suction cups can be used to pickup and hold work pieces with smooth and impervious surfaces	
93	Advantages of air motor		<ul> <li>1.Do not require electrical power</li> <li>2.Can be used in volatile atmospheres.</li> <li>3.Can stall under full load for indefinite periods of time</li> <li>4.Speed can be regulated through simple flow control valve</li> </ul>	
94	Pneumatic cylinders classification		Single acting cylinder, Double acting cylinder, Tandem cylinder, Three position cylinder, Through rod cylinder, Adjustable stroke cylinder, Telescoping cylinder	
95	Purpose of a lubricator		Air is not a good lubricant. So to lubricate the moving parts in the pneumatic system, a fine mist of oil is	

		discharged into the air by a lubricator
96	Function of an air filter	The function of an air filter is to remove contaminants from air before it reaches the pneumatic components such as valves and actuators
97	Function of a dryer	The purpose of the dryer is to reduce the relative humidity and dew point of the compressed air from the compressor
98	Multistage compressor	A compressor that draws in air and compress it to its final pressure in two or more stages is called multistage compressor
99	Types of positive displacement compressors	Reciprocating piston type (ii) Rotary vane type (iii) Rotary screw type
100	Main reason for pneumatics preferred overhydraulics	Pneumatics is preferred, over hydraulics when high speed and lower forces are required and do not require high precision
	UNIT	V: DESIGN OF PNEUMATIC CIRCUITS
101	Hydropneumatics	Systems use air and oil are hydro pneumatics systems
102	Types of Hydro pneumatic circuits	<ul> <li>i) Air-oil reservoir</li> <li>ii) Air-oil cylinder</li> <li>iii) Air-oil intensifier.</li> </ul>
103	Low-Cost Automation	Low-cost automation is defined as a technology that creates some degree of automation around the existing equipment, tools and methods, using mostly the standard equipment available in themarket
104	Trouble shooting	Troubleshooting means an organized and systematic study of the problem and a logical approach to the difficulty faced in the system
105	Causes of noisy pump	1.Misalignment of pump and prime mover2.Air remains in pump casing 3.Pump bolts very loose 4.Very high viscosity of oil 5.Pump running too fast.
106	Causes for low or erratic pressure in a hydraulic system	1.Very low relief valve setting2.Leakage of pump delivery withinthe system3.Pump slipping its entire volume.
107	Causes of erratic motion in pneumatic cylinder	1.Valve sticking or binding 2.Cylinder sticking or binding

108	Methods of entering	<ol> <li>Ladder diagram based.</li> <li>Low-level language based on Boolean expressions</li> </ol>
108	the program in PLC	3.Functional blocks
		4.High-level languages.
		1.Central processing unit with
100	Basic elements of	an associated memory
109	PLC	2.Input modules
		3. Output modules.
		Programmable Logic Controller is
		defined as a digital electronic device
	Programmable Logic	that uses a programmable memory to
110	Controller	store instructions such as logic,
	Controller	sequencing, timing, counting and
		arithmetic to control machine or
		processes
		The ladder diagram is a representation
		of hardware connections between
		switches, relays and solenoids etc.,
111	Ladder diagram	which constitute the basic components
		of an electrical control system. The
		left leg of the ladder connected to the
		power and the right to the ground.
	Description	Timers are used to control the time
112	Purpose of an	duration of a working cycle. In this
	electrical timer	way, a dwell can be provided when needed
		Electrical relay is a switch whose contacts open or close when its coil is
113	Electrical relay	energized. Relays are used for
115	Electrical relay	energizing and de-energizing
		solenoids
		Push button switches are momentary
114	Push button switch	switches. They make or break contact
		only as long as they are held pressed
117	T inside service 1	Limit switches make or break contact
115	Limit switch	permanently when they are actuated.
114	Prossura switch	Pressure switches open or close
116	Pressure switch	contacts based on the system pressure.
		Temperature switches senses change
117	Temperature switch	in temperature and open or close
11/		contacts when a predetermined
		temperature is reached.
		A step counter is a digital modular
		counter constructed from stepping
110		units. A stepping unit is built from
118	Step counter	memory valve and a pre-switched and
		valve with two inputs.
	Common methods	1. Classic method
119	for designing logic	2. Cascade method
-	circuits	3. Step counter method
L	<u> </u>	

		<ul><li>4. KV map method</li><li>5. Combinational circuit design.</li></ul>
120	Symbol for fluidic AND element	-
121	Truth table for fluidic AND element	$\begin{array}{c ccccc} \mathbf{Truth Table} \\ C_1 & C_2 & O_1 & O_2 \\ 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 1 & 1 & 1 & 0 \end{array}$
122	Symbol for fluidic OR element	-
123	Truth table for fluidic OR element	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
124	Moving part logic elements (MPL)	The MPL elements are miniature pneumatic elements. These elements are available as AND, OR, NOT logic elements. The elements use moving parts such as diaphragms, springs, disk, balls, poppet's.
125	Advantages of fluidic elements	<ol> <li>A wear and tear of elements.</li> <li>No actuating force needed.</li> <li>Very little space needed for mounting.</li> <li>Quite insensitive to temperature, vibration, shock, electric noise and radiation</li> </ol>

	QUESTIONS FOR PLACEMENT TRAINING			
126	What are the leading companies in automation field?	<ul> <li>Rockwell Automation.</li> <li>Titan Automation Solution.</li> <li>Voltas Limited.</li> <li>GE India.</li> <li>Honeywell India.</li> <li>Larsen &amp; Toubro.</li> <li>Siemens Limited.</li> <li>ABB Limited.</li> </ul>		
127	Give some examples of pneumatic fittings that we use in our daily life.	<ul> <li>Bicycle/ball pumps</li> <li>Tire pressure gauges</li> <li>Nail guns</li> <li>The handicapped-access buttons which operate automatic doors</li> <li>Vacuum cleaners</li> </ul>		
128	Pneumatic systems usually should not exceed	1 HP		
129	Which gas is used in gas charged accumulator?	Nitrogen		
130	How is pressure of fluid under piston calculated in a weighted accumulator?	Pressure of fluid = (weight added / piston area)		
131	Why the pilot is operated check valve used in clamping operation?	A. To reduce leakage in spool valve B. To avoid decrease in pressure during clamping		
132	When comparing operating cost of hydraulic systems to pneumatic systems, which system is cost effective?	Pneumatic system		
133	Initial setup cost of Pneumatic systems are generally?	Less expensive		
134	The most common hydraulic fluid is	Water		
135	Leakage in rotary chucks can be compensated by	Accumulator		

136	Why is fluid power preferred in mobile vehicles?	Power can be transmitted without any delay When overloaded, fluid power systems stop without damaging the components Fluid is non-compressible
137	Pressure of 1 bar is	14.5 psi
138	What types of pneumatic conveying systems are typically used?	Dilute phase systems and dense phase systems
139	What effect does overloading have on fluid power and electrical systems?	<ul> <li>A. Electrical components get damaged in electrical systems</li> <li>b. Fluid power system stops working without damaging the components</li> </ul>
140	Fluid power circuits use schematic drawings to	Simplify component function details
141	Generally liquids are non-compressible but when a large pressure of 70 bar is applied, petroleum oil can be compressed up to	0.5% of its original volume
142	The resistance offered to the flow of fluid inside a piston develops into?	Pressure
143	What is the relation between speed and flow rate for fixed displacement vane pump?	Flow rate increases with increase in speed of rotor
144	Which type of motion is transmitted by hydraulic actuators?	<ul><li>A. Linear motion</li><li>B. Rotary motion</li></ul>
145	What is the function of electric actuator?	Converts electrical energy into mechanical torque
146	Which energy is converted into mechanical energy by the hydraulic cylinders?	Hydrostatic energy

147	What is the advantage of using a single acting cylinder?	Piston seals are not required	
148	Which stage in two stage direction control valve is solenoid operated?	Pilot stage direction control valve	
149	What does the numbers in 4/2 valve mean?	4 ways and 2 positions	
150	Which type of solenoid has more chances of coil failure?	AC solenoid	